

## MVS 275-LR

### MVS 275-LR



### Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [Flat Deck Double Chamber with Swing-Lid Sheet \(pdf\)](#)

### Contact Us

- ▶ [Request a Quote](#)

### Chamber & Seal Bars

Chamber Width x Length	27.00" x 35.00"
Chamber Height	10.00"
Number of Seal Bars (lid mounted)	2
Position of Seal Bars	Left & Right
Seal Bar Length	2 x 33.00"
Distance between Seal Bars	21.00"
5 mm Seal + 1 mm Cut-Off Seal	✓
Bag Types	Polynylon / Shrink
Quick Change Seal Bars	✓
Independent Power to each Seal Bar	✓

### Performance

Pump Type	Busch R5 Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement @ 50Hz	160 m³/h
Free Air Displacement @ 60Hz	190 m³/h
Pump Power Rating	8 hp
Power Supply	220V / 3ph / 33A

### Display & Controls

Water Resistant Digital Display (IP65)	✓
Selectable Control (Time or %)	✓
Electronic Millibar Sensor	✓
Customizable Programs	9

### Operational Features

Programmable Sealbar Pre-Heat	✓
Programmable Sealing Time	✓
Moisture Quick Stop	✓
Soft Air (slow return of air)	✓
Multi Cycle (pulse vacuuming)	✓
Red Meat Program (prevents air bubbles)	✓
Gas Plus Program (pouch ballooning)	✓
Extra Seal Pressure (14 lbs)	✓
Extra Vacuum (30 sec)	✓
Excess Bag Cut-Off	✓
Fast & Hygienic Lid Evacuation	✓
High Volume Density Plates	✓

### Service

Pump Conditioning	✓
Self Diagnostic	✓
Indicating Display	✓
Toolless Valve Replacement	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓
2nd Year Conditional Warranty**	VP Program

### Housing & Dimensions

Material	Stainless 304
Lid Type / Lid Spring Alignment	Swing Lid / Horizontal
Width x Length	58.75" x 38.75"
Height (Lid open/closed)	53.00" / 43.00"
Working Height	33.00"
Locking Casters	✓
Weight (Net/Shipping)	1250 lbs / 1480 lbs

### Optional Seal Bars

Wide Flat Seal (8 mm)	✓
Dual Flat Seal (2 x 4 mm)	✓
Dual Convex Seal (2 x 3.5 mm)	✓
Top & Bottom Seal	✓

### Optional Features

Inert Gas Flush Kit	✓
Evacuation Filter Kit	✓
Light-Lift Swing Lid (Electronic)	✓
Vinyl Protective Cover	✓
Excess Shrink Bag Cut-Off	✓
Tray for Liquids	-
External Pump Kit	✓
220V Single Phase @ 50/60Hz	-
208V Three Phase @ 50/60Hz	360 m³/h
480V Three Phase @ 50/60Hz	✓

\*Depends on type of product, film and operator ability.

\*\*Through a certified minipack america dealer.

Specifications may change without notice.