

MVS 295-LR

MVS 295-LR



Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [Flat Deck Double Chamber with Swing-Lid Sheet \(pdf\)](#)

Contact Us

- ▶ [Request a Quote](#)

Chamber & Seal Bars

Chamber Width x Length	45.50" x 35.75"
Chamber Height	11.00"
Number of Seal Bars (lid mounted)	2
Position of Seal Bars	Left & Right
Seal Bar Length	2 x 33.00"
Distance between Seal Bars	39.50"
5 mm Seal + 1 mm Cut-Off Seal	✓
Bag Types	Polynylon / Shrink
Quick Change Seal Bars	✓
Independent Power to each Seal Bar	✓

Performance

Pump Type	Busch R5 Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement @ 50Hz	300 m ³ /h
Free Air Displacement @ 60Hz	360 m ³ /h
Pump Power Rating	12 hp
Power Supply	220V / 3ph / 40A

Display & Controls

Water Resistant Digital Display (IP65)	✓
Selectable Control (Time or %)	✓
Electronic Millibar Sensor	✓
Customizable Programs	9

Operational Features

Programmable Sealbar Pre-Heat	✓
Programmable Sealing Time	✓
Moisture Quick Stop	✓
Soft Air (slow return of air)	✓
Multi Cycle (pulse vacuuming)	✓
Red Meat Program (prevents air bubbles)	✓
Gas Plus Program (pouch ballooning)	✓
Extra Seal Pressure (14 lbs)	✓
Extra Vacuum (30 sec)	✓
Excess Bag Cut-Off	✓
Fast & Hygienic Lid Evacuation	✓
High Volume Density Plates	✓

Service

Pump Conditioning	✓
Self Diagnostic	✓
Indicating Display	✓
Toolless Valve Replacement	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓
2nd Year Conditional Warranty**	VP Program

Housing & Dimensions

Material	Stainless 304
Lid Type / Lid Spring Alignment	Swing Lid / Horizontal
Width x Length	95.50" x 38.50"
Height (Lid open/closed)	63.25" / 46.00"
Working Height	33.00"
Locking Casters	✓
Weight (Net/Shipping)	1764 lbs / 2128 lbs

Optional Seal Bars

Wide Flat Seal (8 mm)	✓
Dual Flat Seal (2 x 4 mm)	✓
Dual Convex Seal (2 x 3.5 mm)	✓
Top & Bottom Seal	✓

Optional Features

Inert Gas Flush Kit	✓
Evacuation Filter Kit	✓
Light-Lift Swing Lid (Electronic)	✓
Vinyl Protective Cover	✓
Excess Shrink Bag Cut-Off	✓
Tray for Liquids	-
External Pump Kit	✓
220V Single Phase @ 50/60Hz	-
208V Three Phase @ 50/60Hz	-
480V Three Phase @ 50/60Hz	✓

*Depends on type of product, film and operator ability.
 **Through a certified minipack america dealer.
 Specifications may change without notice.