

Digit 56 Stainless

Digit 56 Stainless



Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [Food Grade Shrink Wrappers Sheet \(pdf\)](#)
- ▶ [Tunnel Series - Hot Air Shrink Systems Sheet \(pdf\)](#)

Video



Wrapping Sandwiches shelf-ready



Wrapping Broccoli shelf-ready

Contact Us

- ▶ [Request a Quote](#)

Sealing Area

Maximum Product Size (W x L x H)	16.00" x 24.50" x 6.25"
Center Folded Film Types	Polyolefin / PVC
Maximum Roll Width	24.00"
Maximum Roll Diameter	12.00"
Adjustable Product Height	✓
Automatic Lid Open	-
Teflon Coated Sealing Blade	✓
Programmable Sealing Blade Temperature	✓

Performance

Wraps per Minute*	up to 30 items
External Pneumatic Seal Pressure Required	✓
Heater Wattage	-
Power Supply	230V / 12A

Display & Controls

Water Resistant Digital Display	LCD
Digital Controls	✓
Customizable Programs	10

Operational Features

Machine Type	Automatic
Automatic: Seal»Cut»Release	✓
Automatic: Seal»Cut»Release»Advance	✓
Sealing Blade Heat	Constant
3 Working Modes (Bag Only/Bag & Shrink/Multiples)	Bag Only
Auto-Entry Conveyor	✓
Auto-Discharge Conveyor	✓
Adjustable Hood Opening	-
Conveyor Belt Modes	Continuous / Step-Advance
Programmable Conveyor Speed	✓
Kissing Belt for Small Items	✓
Overheat Safety Circuit	✓
Photo Cell Activation	✓
Precision Blade Cooling System	-
Tearless Perforation System	✓
Stainless Entry Plate	-
USDA Belting System	✓
Patented Safety System	✓
Lid Closure	Manual

Service

Easy Frontal Access	✓
Indicating Display	✓
Operating/Running/Problem Light	✓
Error Codes	✓
1 Year Limited Warranty	✓

Housing & Dimensions

Material	Stainless 304
Width x Length	78.74" x 39.37"
Height (Lid open/closed)	68.11" / 62.20"
Working Height	34.00"
Locking Casters	✓
Weight (Net/Shipping)	981 lbs / 1146 lbs

Optional Features

Taller Hood	-
Single Hole Punch	Pneumatic
Entry Film Opener	-
Automatic Waste Winder	Standard
Film Waste Ring	-
Product Guide	-
Second Film Roll Kit	-
40" Film Roll Support	-
Entry Belt Scraper and Collector	✓
Printed Film Kit	✓
Shrink System	Tunnel 50 Stainless

*Depends on type of product, film and operator ability. Specifications may change without notice.