

DPY Series

Yamato

Digital Platform Scale

Mate our DPI-500 indicator with our platforms to get the DPY scale you need and save money. Featuring four platform sizes (12" x 12", 13" x 18", 20" x 15" and 18" x 24") and a waterproof, 5000 division, legal for trade, LED indicator with full duplex RS-232C serial communications. The 12" x 12" platform is also legal for trade. Various capacities, up to 600 lb, are available to target your applications.



Features

- Several Platform Sizes
- Multiple Capacities
- Bright LED Display with Annunciators
- Waterproof (NEMA 4X)
- RS-232C Serial Communications
- Push Button Tares
- Legal for Trade (DPY-1212 only)
- AC Adaptor
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Print Key
- Push Button lb/kg toggle

Reliability you can trust

Features

- Several Platform Sizes
- Several Capacities
- Bright LED Display with Annunciators
- Waterproof (NEMA 4X)
- RS-232C Serial Communications
- Push Button Tares
- Legal for Trade (DPY-1212 only)
- AC Adaptor
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Print Key
- Push Button lb/kg toggle

Options

Other Platform Sizes and Capacities Available Upon Request

Specifications

Model	DPY-1212	DPY-1318	DPY-2015	DPY-1824
Accuracy Class	Class III, 5,000 Divisions	up to 10000 divisions		
Certificate of Conformance #	USA: 96-163 (DPI-500) 99-028 (DP-1212) Canada: AM-5290	Not Certified Legal for Trade		
Capacity and Divisions	25 lb x 0.005 lb 50 lb x 0.01 lb 100 lb x 0.02 lb 150 lb x 0.05 lb	200 lb x 0.02 lb 400 lb x 0.05 lb	100 lb x 0.02 lb 250 lb x 0.05 lb 400 lb x 0.1 lb	100 lb x 0.02 lb 400 lb x 0.05 lb 600 lb x 0.1 lb
	15 kg x 0.005 kg 25 kg x 0.005 kg 50 kg x 0.01 kg 75 kg x 0.05 kg	100 kg x 0.02 kg 200 kg x 0.02 kg	50 kg x 0.01 kg 150 kg x 0.05 kg 200 kg x 0.05 kg	50 kg x 0.01 kg 200 kg x 0.02 kg 300 kg x 0.05 kg
Weighing System	Strain gauge load cell			
Platform	12" x 12" stainless steel, removable (305 x 305 mm)	13" x 18" stainless steel, removable (330 x 457 mm)	20" x 15" stainless steel (508 x 381 mm)	18" x 24" stainless steel, removable (457 x 610 mm)
Display	LED: 6 digits plus annunciators Character size: 0.6" x 0.4"			
Power	AC adaptor			
Operating Temperatures	14° F ~ 104° F (-10° C ~ 40° C)			