

DSR Series

Yamato

Bench/Receiving Scale

The DSR series features a large 12" x 12" removable, stainless steel platform that fits almost anywhere and a slanted face with a large, easy to read display. The indicator is connected to the platform by a 9 foot coiled cord that allows for convenient, remote placement. A keypad toggle selects pound or kilo-gram units, and the DSR-400 has an optional foot tare switch for hands free operation. An AC adaptor is included with the scale.

Features

- Removable Stainless Steel Platform
- Easy to Read LCD Display with Annunciators
- AC Adaptor or Battery Operation
- 9 Foot Coiled Indicator Cord
- Low Profile Design
- Push Button Unit Toggle (lb and kg)
- Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms



Reliability you can trust

Features

- Removable Stainless Steel Platform
- Easy to Read LCD Display with Annunciators
- AC Adaptor or Battery Operation (Adaptor included)
- 9 Foot Coiled Indicator Cord
- Low Profile Design
- Push Button Unit Toggle (lb and kg)
- Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms

Options

- Foot Tare Switch



Specifications

| Model | DSR-200 | DSR-400 |
|------------------------|-----------------------------------------------------------|----------------------------------------------------------------------------------------------|
| Accuracy | 1000 Divisions | Dual Range |
| Capacity and Divisions | 0-200 lb x 0.2 lb 0-100 kg x 0.1 kg | 0 - 220 lb x 0.5 lb 220 - 400 lb x 1.0 lb 0 - 100 kg x 0.2 kg 100 - 180 kg x 0.5 kg |
| Weighing System | Strain gauge load cell | |
| Platform | 12" x 12.25" stainless steel, removable (305 x 311 mm) | |
| Display | Liquid crystal display: 4 digits plus annunciators | |
| Character Size | 0.9" x 0.4" | 0.5" x 0.2" |
| Power | 6 "AA" batteries, AC adaptor (included) | |
| Operating Temperatures | 32°F ~ 104°F (0°C ~ 40°C) | |