

MSK Series- Injector

Standard Features:

- ✓ Stainless Steel Construction
- ✓ Servo Drive
- ✓ High Quality Stainless Steel Centrifugal Pump
- ✓ Stainless Steel Brine Tank
- ✓ Variable Speed Drive up to 50 Strokes per minute
- ✓ Easy to Read and Operate Control Panel
- ✓ Easy to Clean with Removable Injection Heads/Needles and Walking Beam
- ✓ Closed Brine Circulation System



** MSK-44 Pictured

Technical Data	MSK-22	MSK-44	MSK-88
Number of Injection Needles	22	44	88
Motor Power	2.2 KW	2.4 KW	3.0 KW
Brine Pump Power	1.85 KW	1.85 KW	1.85 KW
Walking Beam Width	12.5"/ 320mm	14"/ 360mm	20.5"/520mm
Speed	1-40 Strokes/ min.	1-50 Strokes/ min.	1-50 Strokes/ min.
Product Clearance	10"/260mm	10.75"/270mm	10.75"/270mm
Injection Volume	8-45%	5-60%	5-70%
Pressure Rating	0-40 PSI	0-60 PSI	0-60PSI
Brine Tank Capacity	140 L	200 L	220 L
Machine Size	84"L x 28"W x84"H	84"L x30"W x86"H	84"L x35"W x86"H

All specifications are subject to change without notice

PROMARKS INC.