

PPC Series

PPC-300WP

Yamato

Washdown Portable Portion Control Scale

The PPC-300WP alternates between checkweighing, grading and fixed weighing functions at the touch of a button, and is washdown safe. It is available in models ranging from 2 kg to 20 kg and is NTEP certified at 2,000 divisions. Results can be displayed in several units and standard features include battery status indicator, bubble level and a bar chart display which provides a graphical representation of various weighing functions; all with Yamato reliability you can trust.

Features

- Over/Under Indicator
- Large Removable Stainless Steel Platform
- Accurate - 2,000 Divisions
- Large LCD Display
- Battery or AC Operation
- Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Multiple Units
- Capacities from 4.4 lb to 44 lb (2 kg to 20 kg)
- IP68/65 Waterproof ¹



Reliability you can trust

Features

- Over/Under Indicator
- Large Removable Stainless Steel Platform
- Accurate - 2,000 Divisions
- Large LCD Display
- Battery Operation
- Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Multiple Units
- Capacities from 2 kg to 20 kg (4.4 lb to 44 lb)
- IP68/65 Waterproof ¹

Options

- AC Adaptor

Specifications

Model	PPC-300WP				
	Pound	Kilogram	Ounce	Pound-Ounce *	Max. Tare
PPC-300WP-4	4.4 lb x 0.002 lb	2 kg x 0.001 kg	80 oz x 0.05 oz	5 lb x 0.05 oz	Capacity
PPC-300WP-10	10 lb x 0.005 lb	4 kg x 0.002 kg	160 oz x 0.1 oz	10 lb x 0.1 oz	Capacity
PPC-300WP-22	22 lb x 0.01 lb	10 kg x 0.005 kg	352 oz x 0.2 oz	22 lb x 0.2 oz	Capacity
PPC-300WP-44	44 lb x 0.02 lb	20 kg x 0.01 kg	704 oz x 0.5 oz	44 lb x 0.5 oz	Capacity
* Combined units, such as pound-ounce, are not legal for trade					
Accuracy Class	Class III, 2000 divisions				
C of C	08-041				
Weighing System	Strain gauge load cell				
Platform	9" x 7.625" stainless steel (230 x 194 mm)				
Display	7 segment LDC single display				
	Character Size: 0.5"x 1.2" 5 digits (13.5 x 30 mm) (W x L)				
Power	6 VDC- four "D" size batteries or optional AC adaptor				
Operating Temperatures	14° F to 104° F (-10° C to 40° C)				
Battery Life	1400 hours of continuous use with alkaline batteries				
Function	checkweighing, grading, packing; unit toggle, function toggle				

¹ PPC-300WPs are manufactured as IP68. If the units are opened they can either be closed on-site for an IP65 rating, or returned to Yamato for re-sealing which will assure continued IP68 protection.

Only Yamato authorized technicians using Yamato approved equipment can assure the integrity of the IP68 protective seal on this unit after it has been opened; opening of this unit by anyone else will void the IP68 warranty against internal water damage.