

# PPC Series

## PPC-300

**Yamato**

### Portable Portion Control Scale

The PPC-300 alternates between checkweighing, grading and fixed weighing functions at the touch of a button. It is available in models ranging from 2 kg to 30 kg and is NTEP certified at 2,000- 3000 divisions. Results can be displayed in several units and standard features include battery status indicator, bubble level and a bar chart display which provides a graphical representation of various weighing functions; all with Yamato reliability you can trust.

### Features

- Over/Under Indicator
- Large Removable Stainless Steel Platform
- Accurate - 2,000 to 3,000 Divisions
- Large LCD Display
- Battery or AC Operation
- Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Multiple Units
- Optional Dual Display for Retail Services
- Capacities from 4.4 lb to 60 lb (2 kg to 30 kg)



*Reliability you can trust*

## Features

- Over/Under Indicator
- Large Removable Stainless Steel Platform
- Accurate - 2,000 to 3,000 Divisions
- Large LCD Display
- Battery or AC Operation
- Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Multiple Units (toggle switch)
- Optional Display for Retail Services
- Capacities from 2 kg to 30 kg (4.4 lb to 60 lb)

## Options

- Dual Indicator for Retail Settings
- AC Adaptor

## Specifications

Model	PPC-300 / PPC-300D <sup>1</sup>				
	Pound	Kilogram	Ounce	Pound-Ounce *	Max. Tare
PPC-300-4, PPC-300D-4	4.4 lb x 0.002 lb	2 kg x 0.001 kg	80 oz x 0.05 oz	5 lb x 0.05 oz	Capacity
PPC-300-10, PPC-300D-10	10 lb x 0.005 lb	4 kg x 0.002 kg	160 oz x 0.1 oz	10 lb x 0.1 oz	Capacity
PPC-300-22, PPC-300D-22	22 lb x 0.01 lb	10 kg x 0.005 kg	352 oz x 0.2 oz	22 lb x 0.2 oz	Capacity
PPC-300-44, PPC-300D-44	44 lb x 0.02 lb	20 kg x 0.01 kg	704 oz x 0.5 oz	44 lb x 0.5 oz	Capacity
PPC-300-60, PPC-300D-60	60 lb x 0.02 lb	30 kg x 0.01 kg	1056 oz x 0.5 oz	66 lb x 0.5 oz	Capacity
* Combined units, such as pound ounce, are not legal for trade					
Accuracy Class	4.4, 10, 22 and 44 lb models: Class III, 2000 divisions 60 lb model: Class III, 3000 divisions				
C of C #	08-041				
Weighing System	Strain gauge load cell				
Platform	9" x 7.625" stainless steel (230 x 194 mm)				
Display	PPC-300: 7 segment LDC, Single Display PPC-300D: 7 segment LDC, Dual Display				
	Character Size: 0.5"x 1.2" 5 digits (13.5 x 30 mm) (W x L)				
Housing Material	ABS Plastic				
Power	6 VDC- four "D" size batteries or optional AC adaptor				
Operating Temperatures	14° F to 104° F (-10° C to 40° C)				
Battery Life	1400 hours of continuous use with alkaline batteries				
Function	checkweighing, grading, packing; unit toggle, function toggle				

<sup>1</sup> D = dual display