

SS-50/ SS-100 Piston Stuffer

Standard Features:

- Hands-free operation through use of conveniently located knee lever to control stuffing action
- Adjustable speed and pressure
- Assortment of three straight horns in 12mm, 20mm and 50mm sizes of product versatility
- Easily removable piston and lid gaskets for quick and easy cleaning
- Drain hole in bottom of cylinder for easy washdown
- Design that makes oil changes easy, plus replaceable oil filters

Options:

- Volumetric portioner-ideal for accurate weight packaging of products such as ground meat and poultry, cheese and dough. Creates units portions ranging in weight from 5 to 17 ounces per stroke



Technical Data		
Model	SS-50	SS-100
Stuffing Capacity	250-lbs./hr	400-lbs./hr
Portable	Yes	No
Variable Speed	Yes	Yes
Stuffing Tubes	3	3
Max. Tube Diameter	1.14"/ 29mm	1.85"/ 47mm
Tube Height	49.8"/ 1265mm	49.8"/ 1265mm
Stuffer Width	20.5"/ 522mm	21.8"/ 555mm
Stuffer Depth	29.9"/ 760mm	36.5/ 928mm
Lever Type	Knee	Knee
Cylinder Vent	Yes	Yes
Horsepower	1.0	2.0
Voltage	220/1ph/50-60hz	220/1ph/50-60hz
Amps	5.6	9
Oil Capacity	4.62	5.94
Net Weight	353 lbs/ 160kg	551 lbs/250kg