

Cyclone 40

Cyclone 40



Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [External & Compact Chamber Sheet \(pdf\)](#)

Contact Us

- ▶ [Request a Quote](#)

Chamber & Seal Bars

Chamber Width x Length	-
Height (Chamber + Dome/Lid = Total)	-
Number of Seal Bars	1
Position of Seal Bars	Front
Seal Bar Length	17.00"
4 mm Seal + 1 mm Cut-Off Seal	-
4 mm Seal	✓
Bag Types	Channel

Performance

Pump Type	Dry Piston
Cycles per Minute*	up to 2
Internal Cooling Fan	✓
Free Air Displacement @ 50Hz	-
Free Air Displacement @ 60Hz	0.6 m ³ /h
Pump Power Rating	350W
Power Supply	115V / 3A

Display & Controls

Water Resistant Digital Display	✓
LED Display	✓
Customizable Programs	4
Auto/Manual Selection	✓

Operational Features

Programmable Sealing Time	✓
Programmable Vacuum Time	✓
Moisture Collector	✓
External Vacuum Program	✓
External Channel Bag Evacuation	✓
Excess Bag Cut-Off	-
High Volume Density Plates	-

Service

Pump Conditioning	-
Indicating Display	✓
1 Year Limited Warranty	✓

Housing & Dimensions

Material	Aluminum
Lid Type	-
Width x Length	19.00" x 7.50"
Height (Lid open/closed)	-
Weight (Net/Shipping)	12 lbs / 16 lbs

Optional Features

Dual Flat Seal (2 x 4 mm)	-
Dual Convex Seal (2 x 3.5 mm)	-
Tray for Liquids	-
220V Single Phase @ 50/60Hz	✓

*Depends on type of product, film and operator ability.
 Specifications may change without notice.