

1832 N. Glassell Street · Orange, CA 92865, USA Call: +1.714.283.4200 · Fax: +1.714.283.4268 info@minipack.us · www.minipack.us

Galileo Food



Downloads

- Product Sheet (pdf)
- Food Grade Shrink Wrappers Sheet (pdf)

Contact Us

Request a Quote

Sealing Area	
Maximum Product Size (W x L x H)	20.00" x 16.00" x 8.00"
Center Folded Film Types	Polyolefin / PVC
Maximum Roll Width	24.00"
Maximum Roll Diameter	10.00"
Adjustable Product Height	1
Automatic Lid Open	1
Teflon Coated Sealing Blade	1
Programmable Sealing Blade Temperature	1
Performance	
Wraps per Minute*	up to 6 items
External Pneumatic Seal Pressure Required	No
Heater Wattage Power Supply	2550W 220V / 14A
	220V / 14A
Display & Controls	
Water Resistant Digital Display	LED
Digital Controls	/
Customizable Programs	10
Operational Features	
Machine Type	Manual
Automatic: Seal»Cut»Release	1
Automatic: Seal»Cut»Release»Advance	-
Sealing Blade Heat	Impulse
3 Working Modes (Bag Only/Bag & Shrink/Multiples)	1
Auto-Entry Conveyer	-
Auto-Discharge Conveyer	-
Adjustable Hood Opening	1
Conveyor Belt Modes	-
Programmable Conveyer Speed	-
Kissing Belt for Small Items	-
Overheat Safety Circuit	1
Photo Cell Activation	-
Precision Blade Cooling System	Air
Tearless Perforation System Stainless Entry Plate	
USDA Belting System	-
Patented Safety System	-
Lid Closure	Manual
Service	
	1
Easy Frontal Access Indicating Display	✓ ✓
Operating/Running/Problem Light	-
Error Codes	1
1 Year Limited Warranty	· · · · · · · · · · · · · · · · · · ·
Housing & Dimensions	
Material	Fiberglass / Enameled
Width x Length	45.00" x 33.50"
Height (Lid open/closed)	52.00" / 46.00"
Working Height	35.00"
Locking Casters	1
Weight (Net/Shipping)	188 lbs / 284 lbs
Optional Features	
Taller Hood	Reverse Hood
Single Hole Punch	115V
Entry Film Opener	1
Automatic Waste Winder	1
Film Waste Ring	1
Product Guide	1
Second Film Roll Kit	8.00" Diameter Roll
40" Film Roll Support	-
Entry Belt Scrapper and Collector	-
Printed Film Kit	-
*Depends on type of product, film and operator ability.	-

*Depends on type of product, film and operator ability. Specifications may change without notice.