

FEATURES

- Dynamic non-stop weigh labelling
- 3 preset speeds by PLU
- Historically controlled thermal head (resulting in very high print quality)
- Direct thermal/thermal transfer operation
- Touch screen display
- Choice of label applicators
- Interface card for computer linking
- Powered printer height adjustment
- Easy set-up and operation
- Product sensing by photocell
- Self contained console and electronics
- Easy to clean and maintain
- Stainless steel and anodised aluminium construction



FULLY AUTOMATIC HIGH SPEED PRINT AND APPLY LABEL SYSTEM

The HI-3600E is a fully automatic high speed machine, weighing and labelling at up to 100 packs per minute.

It is designed for continuous industrial use in combination with most types of packaging machines within the meat, poultry, fruit, vegetable and fish sectors.

The HI-3600E retains DIGI's renowned level of quality, reliability and efficiency. It is extremely versatile and flexible and is very easy to operate.

PRODUCT INFORMATION

OPTIONS:

- Second Labeller
- LA-2600 Can Be Fitted As Second Labeller
- Backfeed Kit
- Printer Door Kit
- Thermal Transfer
- Gravity Outfeed
- Pre-Infed Conveyor
- Average Weight Software

DIGI EUROPE LTD
 Digi House
 Rookwood Way
 Haverhill
 Suffolk CB9 8DG
 England

Tel : +44 (0) 1440 712175
 Fax: +44 (0) 1440 712174
 sales@digico.uk
 www.digi-systems.com



SPECIFICATION

Capacity Interval:	2kg (0-1kg/1g), 1-2kg/2g dual range or 4kg (0-2kg/2g, 2-4kg/5g option - consult DEL sales) or 15lb/0.01lb (option - consult DEL sales).
Print Method:	60mm (7.4 dots/mm) thermal head or 75mm (6 dots/mm) thermal head.
Pack Size:	80-300mm (3.15"-11.81") long 40-250mm (1.57"-9.84") wide 180mm (7.09") high maximum.
Label Size:	Min. 30mm (1.18") wide x 28mm (1.10") high Max. 120mm (4.72") wide x 130mm (5.12") high.
Application System:	Airjet, airstamp, concave or touch.
Label Format:	12 standard formats and 20 additional fully programmable formats.
Memory Items:	2MB standard (max 6MB option).
Preset Data Incl:	PLU code, price, pack quantity, pack date, sell by date, time, shop name, commodity name etc.
Pack Speed:	Up to 100 packs per minute.
Label Roll:	Roll diameter 300mm Core diameter 76mm Outside or inside wound.
Power:	220-240V (or 115V option) 50/60Hz AC single phase.

