

## MDT 60

MDT 60



### Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [Hot Water Shrink Systems Sheet \(pdf\)](#)

### Contact Us

- ▶ [Request a Quote](#)

Tank	
Tank Dimensions (W x L x H)	19.70" x 23.60" x 16.50"
Tank Volume	25 Gallons
Dip Depth	8.60"
Heating System Integration	Integrated
Minimum Immersion Height	-
Performance	
Max. Temperature	203°F
Temperature Control Increments	0.1°F
Temperature Stability	-
Lifting System	Hydraulic
Maximum Weight Load	220 lbs
Insulating Polypropylene Balls	✓
Cycle Time	2.7 sec
Circulation Pump	No circulation
Pressure Flow Rate (Max.)	-
Heater Output	2 x 4500W
Power Rating	9 KW
Power Supply	220V / 3ph / 25A
Display & Controls	
Display Type	LCD
Display Size	1.57" x 0.75"
Backlit Display	✓
Selectable Temperature Readings (°C/°F)	✓
Easy Up and Down Buttons	✓
Alarm and Fault Indicators	✓
Operational Features	
Low Liquid Level Safety	✓
Over Temperature Protection	Limited to 203°F
Failsafe Heater Control	-
Service	
Easy Frontal Access	✓
Error Codes	✓
1 Year Limited Warranty	✓
Housing & Dimensions	
Material	Stainless 304
Machine Size (W x L x H)	29.00" x 30.00" x 41.50"
Locking Casters	✓
Weight (Net/Shipping)	265 lbs / 324 lbs
Optional Features	
240V Power Supply	-
Custom Lid for Cambro Tanks	-
Travel & Storage Case	-
Double-Wall Cooking Tank (Stainless)	-

Specifications may change without notice.