

Media

Media



Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [Integrated L-Sealer with Heat Tunnel Sheet \(pdf\)](#)

Contact Us

- ▶ [Request a Quote](#)

Sealing Area

Maximum Product Size (W x L x H)	22.00" x 16.00" x 9.00"
Center Folded Film Types	Polyolefin / PVC
Maximum Roll Width	24.00"
Maximum Roll Diameter	10.00"
Adjustable Product Height	✓
Programmable Seal Arm Opener	✓
Teflon Coated Sealing Blade	✓
Programmable Sealing Blade Temperature	✓

Performance

Wraps per Minute*	up to 16 items
1 Power Source	✓
External Pneumatic Seal Pressure Required	No
Heater Tunnel Wattage	5700W
Power Supply	208V / 3ph / 20A

Display & Controls

Water Resistant LED Display	✓
Digital Controls	✓
Customizable Programs	6

Operational Features

Machine Type	Semi-Automatic
Automatic: Seal»Cut»Release»Advance	✓
Sealing Blade Heat	Impulse
3 Working Modes	Bag Only / Bag & Shrink / Multiples
Precision Blade Cooling System	Coolant Fluid
Sealing Activation Modes	Timer / Push Button / Foot Pedal (optional)
Automatic Seal Arm Closure	✓
Automatic Cool-Down	✓
Conveyor Belt Modes	Continuous / Step-Advance
Auto-Discharge Conveyor	✓
Programmable Conveyor Speed	✓
Overheat Safety Circuit	✓
Automatic Waste Winder	✓
Tearless Perforation System	✓
Double-Insulated Tunnel Walls	✓
18" Exit Roll Conveyor	✓
Stainless Entry Plate	✓
Patented Safety System	✓

Service

Easy Frontal Access	✓
Indicating Display	✓
Error Codes	✓
1 Year Limited Warranty	✓

Housing & Dimensions

Material	Steel / Baked Enamel
Width x Length	91.00" x 28.50"
Height (Lid open/closed)	54.50" / 34.50"
Working Height	32.00"
Locking Casters	✓
Weight (Net/Shipping)	632 lbs / 755 lbs

Optional Features

Single Hole Punch	115V
Foot Pedal	✓
Entry Film Opener	✓
Teflon Belt for Tunnel	✓

*Depends on type of product, film and operator ability.
 Specifications may change without notice.