

MVS 20

MVS 20



Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [External & Compact Chamber Sheet \(pdf\)](#)

Contact Us

- ▶ [Request a Quote](#)

Chamber & Seal Bars

Chamber Width x Length	8.75" x 12.00"
Height (Chamber + Dome/Lid = Total)	3.00" + 1.00" = 4.00"
Number of Seal Bars	1 (Removable)
Position of Seal Bars	Front
Seal Bar Length	8.50"
4 mm Seal + 1 mm Cut-Off Seal	✓
4 mm Seal	-
Bag Types	Polynylon / Shrink / Channel

Performance

Pump Type	Busch KB Oil Rotary
Cycles per Minute*	up to 3
Internal Cooling Fan	✓
Free Air Displacement @ 50Hz	4.0 m ³ /h
Free Air Displacement @ 60Hz	4.8 m ³ /h
Pump Power Rating	0.25 hp
Power Supply	115V / 6A

Display & Controls

Water Resistant Digital Display	✓
LED Display	✓
Customizable Programs	1
Auto/Manual Selection	✓

Operational Features

Programmable Sealing Time	✓
Programmable Vacuum Time	-
Moisture Collector	-
External Vacuum Program	-
External Channel Bag Evacuation	✓
Excess Bag Cut-Off	✓
High Volume Density Plates	✓

Service

Pump Conditioning	✓
Indicating Display	✓
1 Year Limited Warranty	✓

Housing & Dimensions

Material	Stainless 304
Lid Type	Transparent with Dome
Width x Length	10.75" x 17.25"
Height (Lid open/closed)	19.00" / 9.50"
Weight (Net/Shipping)	47 lbs / 50 lbs

Optional Features

Dual Flat Seal (2 x 4 mm)	✓
Dual Convex Seal (2 x 3.5 mm)	✓
Tray for Liquids	✓
220V Single Phase @ 50/60Hz	✓

*Depends on type of product, film and operator ability.
 Specifications may change without notice.