

## MVS 26X

### MVS 26X



### Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [MVS X-Series Table Top Chamber Sheet \(pdf\)](#)

### Contact Us

- ▶ [Request a Quote](#)

### Chamber & Seal Bars

Chamber Width x Length	10.75" x 16.00"
Height (Chamber + Dome/Lid = Total)	4.25" + 1.00" = 5.25"
Number of Seal Bars (removable)	1
Position of Seal Bars	Front
Seal Bar Length	10.50"
Distance between Seal Bars	-
4 mm Seal + 1 mm Cut-Off Seal	✓
Unique Waffle-Pattern Sealing	✓
Hygienic Seamless Chamber	-
Bag Types	Polynylon / Shrink / Channel
Pop-Out Seal Bars	✓
Independent Power to each Seal Bar	✓

### Performance

Pump Type	Busch KB Oil Rotary
Cycles per Minute*	up to 2
Free Air Displacement @ 50Hz	6 m <sup>3</sup> /h
Free Air Displacement @ 60Hz	7 m <sup>3</sup> /h
Pump Power Rating	0.25 hp
Power Supply	115V / 12A

### Display & Controls

Water Resistant Digital Display	✓
LED Display	✓
Electronic Millibar Sensor	✓
Customizable Programs	9

### Operational Features

Programmable Sealing Time	✓
Programmable Vacuum Time (%)	✓
External Channel Bag Evacuation	✓
Extra Vacuum (30 sec)	✓
Excess Bag Cut-Off	✓
High Volume Density Plates	✓

### Service

Pump Conditioning	-
Indicating Display	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓

### Housing & Dimensions

Material	Stainless 304
Lid Type	Transparent with Dome
Width x Length	15.00" x 22.50"
Height (Lid open/closed)	24.50" / 12.00"
Recessed Lifting Cups	-
Leveling Legs	✓
Weight (Net/Shipping)	74 lbs / 83 lbs

### Optional Seal Bars

Wide Flat Seal (6mm + 1mm Cut-Off Seal)	✓
Dual Flat Seal (2 x 4 mm)	✓
Dual Convex Seal (2 x 3,5 mm)	✓
Top & Bottom Seal	-

### Optional Features

Inert Gas Flush Kit	✓
Evacuation Filter Kit	-
Tray for Liquids	✓
NSF 4" Legs	-
220V Single Phase @ 50/60Hz	-

\*Depends on type of product, film and operator ability.  
 Specifications may change without notice.