

MVS 38

MVS 38



Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [MVS X-Series Table Top Chamber Sheet \(pdf\)](#)

Contact Us

- ▶ [Request a Quote](#)

Chamber & Seal Bars

Chamber Width x Length	14.75" x 13.00"
Height (Chamber + Dome/Lid = Total)	3.75"
Number of Seal Bars (removable)	1
Position of Seal Bars	Front
Seal Bar Length	16.75"
Distance between Seal Bars	-
4 mm Seal + 1 mm Cut-Off Seal	✓
Unique Waffle-Pattern Sealing	-
Hygienic Seamless Chamber	-
Bag Types	Polynylon / Shrink
Pop-Out Seal Bars	✓
Independent Power to each Seal Bar	✓

Performance

Pump Type	Busch KB Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement @ 50Hz	20 m³/h
Free Air Displacement @ 60Hz	24 m³/h
Pump Power Rating	1.00 hp
Power Supply	115V / 14A

Display & Controls

Water Resistant Digital Display	✓
LED Display	✓
Electronic Millibar Sensor	✓
Customizable Programs	9

Operational Features

Programmable Sealing Time	✓
Programmable Vacuum Time (%)	✓
External Channel Bag Evacuation	-
Extra Vacuum (30 sec)	✓
Excess Bag Cut-Off	✓
High Volume Density Plates	-

Service

Pump Conditioning	✓
Indicating Display	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓

Housing & Dimensions

Material	Stainless 304
Lid Type	Transparent
Width x Length	19.00" x 23.50"
Height (Lid open/closed)	-
Recessed Lifting Cups	-
Leveling Legs	✓
Weight (Net/Shipping)	170 lbs / 225 lbs

Optional Seal Bars

Wide Flat Seal (6mm + 1mm Cut-Off Seal)	-
Dual Flat Seal (2 x 4 mm)	✓
Dual Convex Seal (2 x 3.5 mm)	✓
Top & Bottom Seal	✓

Optional Features

Inert Gas Flush Kit	✓
Evacuation Filter Kit	✓
Tray for Liquids	Forming Box
NSF 4" Legs	-
220V Single Phase @ 50/60Hz	✓

*Depends on type of product, film and operator ability.
 Specifications may change without notice.