

MVS 52XP-DV

MVS 52XP-DV



Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [MVS XP-Series Freestanding Chamber with Label Printer Sheet \(pdf\)](#)

Contact Us

- ▶ [Request a Quote](#)

Chamber & Seal Bars

Chamber Width x Length	20.00" x 21.00" (2x)
Height (Chamber + Dome/Lid = Total)	3.50" + 3.00" = 6.50"
Number of Seal Bars (removable)	4
Position of Seal Bars	Left & Right
Seal Bar Length	4 x 21.00"
Distance between Seal Bars	16.00"
4 mm Seal + 1 mm Cut-Off Seal	✓
Unique Waffle-Pattern Sealing	✓
Bag Types	Polynylon / Shrink
Pop-Out Seal Bars	✓
Independent Power to each Seal Bar	✓

Performance

Pump Type	Busch R5 Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement @ 50Hz	40 m ³ /h
Free Air Displacement @ 60Hz	48 m ³ /h
Pump Power Rating	2 hp
Power Supply	208V / 3ph / 18A

Display & Controls

Water Resistant Digital Display	✓
LCD Full Description Display	✓
Selectable Control (mbar or %)	✓
Electronic Millibar Sensor	✓
Customizable Programs	100

Operational Features

Programmable Direct Thermal Printer	✓
Printing Features: Item Name, Date Coding, Ingredients, Operator Code, Unit Pricing	✓
Programmable Sealing Time	✓
Programmable Vacuum Time (mbar or %)	✓
Moisture Quick Stop	✓
Programmable Hot Food Cycle	✓
Programmable Infusion Cycle	✓
Soft Air (slow return of air)	✓
Extra Vacuum (30 sec)	✓
Excess Bag Cut-Off	✓
High Volume Density Plates	✓

Service

Pump Conditioning	✓
Self Diagnostic	✓
Indicating Display	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓
2nd Year Conditional Warranty**	VP Program

Housing & Dimensions

Material	Stainless 304
Lid Type	Transparent with Dome
Width x Length	51.00" x 31.00"
Height (Lid open/closed)	52.50" / 38.75"
Working Height	35.00"
Locking Casters	✓
Weight (Net/Shipping)	591 lbs / 692 lbs

Optional Seal Bars

Wide Flat Seal (6mm + 1mm Cut-Off Seal)	✓
Dual Flat Seal (2 x 4 mm)	✓
Dual Convex Seal (2 x 3.5 mm)	✓
Top & Bottom Seal	✓

Optional Features

Inert Gas Flush Kit	✓
Evacuation Filter Kit	✓
Tray for Liquids	✓
Taller Dome	-
220V Single Phase @ 50/60Hz	48 m ³ /h
208V Three Phase @ 50/60Hz	75 m ³ /h

*Depends on type of product, film and operator ability.
 **Through a certified minipack america dealer.
 Specifications may change without notice.