

## MVS 65X

### MVS 65X



### Downloads

- ▶ [Product Sheet \(pdf\)](#)
- ▶ [MVS X-Series Freestanding Chamber Sheet \(pdf\)](#)

### Contact Us

- ▶ [Request a Quote](#)

### Chamber & Seal Bars

Chamber Width x Length	29.00" x 27.00"
Height (Chamber + Dome/Lid = Total)	5.00" + 5.00" = 10.00"
Number of Seal Bars (removable)	2
Position of Seal Bars	Left & Right
Seal Bar Length	2 x 25.75"
Distance between Seal Bars	24.00"
4 mm Seal + 1 mm Cut-Off Seal	✓
Unique Waffle-Pattern Sealing	✓
Bag Types	Polynylon / Shrink
Pop-Out Seal Bars	✓
Independent Power to each Seal Bar	✓

### Performance

Pump Type	Busch R5 Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement @ 50Hz	63 m <sup>3</sup> /h
Free Air Displacement @ 60Hz	75 m <sup>3</sup> /h
Pump Power Rating	3 hp
Power Supply	208V / 3ph / 17A

### Display & Controls

Water Resistant Digital Display	✓
LED Full Description Display	✓
Electronic Millibar Sensor	✓
Customizable Programs	9

### Operational Features

Programmable Sealing Time	✓
Programmable Vacuum Time (mbar or %)	✓
Moisture Quick Stop	✓
Soft Air (slow return of air)	✓
Excess Bag Cut-Off	✓
High Volume Density Plates	✓

### Service

Pump Conditioning	✓
Self Diagnostic	✓
Indicating Display	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓

### Housing & Dimensions

Material	Stainless 304
Lid Type	Transparent with Dome
Width x Length	32.00" x 35.00"
Height (Lid open/closed)	58.25" / 41.25"
Working Height	35.00"
Locking Casters	✓
Weight (Net/Shipping)	554 lbs / 633 lbs

### Optional Seal Bars

Wide Flat Seal (6mm + 1mm Cut-Off Seal)	✓
Dual Flat Seal (2 x 4 mm)	✓
Dual Convex Seal (2 x 3.5 mm)	✓
Top & Bottom Seal	✓

### Optional Features

Inert Gas Flush Kit	✓
Evacuation Filter Kit	✓
Tray for Liquids	✓
Taller Dome	✓
220V Single Phase @ 50/60Hz	75 m <sup>3</sup> /h
208V Three Phase @ 50/60Hz	120 m <sup>3</sup> /h

\*Depends on type of product, film and operator ability.  
 Specifications may change without notice.